Campaign Number

The **Campaign Number** object is supported by the MiRTA PBX OpenAPI endpoint. This object is tenant-scoped. Tenant API keys must include `tenant=CANISTRACCI`; writes require a writable API key.

Object Summary

Property	Value
Object	`campaignnumber`
Primary path	`/campaignnumbers`
ID field	`cn_id`
Label field	`cn_number`
Primary source table	`cn_campaignnumbers`
Required on create	`cn_ca_id`, `cn_number`
Path aliases	`/campaignnumber`, `/campaignnumbers`, `/campaign_number`, `/campaign_numbers`

Endpoint Patterns

Action	Example pattern
List	`GET https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI`
Get by ID	`GET https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI`
Create	`POST https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI`
Update	`PATCH https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI`
Delete	`DELETE https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI`

Accepted Field Aliases

Request field	Source field
`campaign_id`	`cn_ca_id`
`number`	`cn_number`
`description`	`cn_description`
`disposition`	`cn_disposition`
`attempts`	`cn_attempts`
`lastattempt`	`cn_lastattempt`
`billsec`	`cn_billsec`

Examples

List Campaign Numbers

Returns the campaign numbers visible to the key and scope.

```
curl -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI"
```

Get Campaign Number

Reads one object by its internal ID.

```
curl -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI"
```

Create Campaign Number

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \
  -H "X-API-Key: TENANT_API_KEY" \
```

```
  -H "Content-Type: application/json" \
  -d '{
  "campaign_id": 44,
  "number": "+15557654321",
  "description": "Docs API campaign target"
}' \
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI"
```

Edit Campaign Number

Updates only the supplied fields.

```
curl -X PATCH \
  -H "X-API-Key: TENANT_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
  "disposition": "CALLBACK",
  "attempts": 1
}' \
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI"
```

Delete Campaign Number

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \
  -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI"
```

List Campaign Numbers for One Campaign

Filters the list by the parent campaign ID. The aliases caid and cn_ca_id are also accepted.

```
curl -X GET \
  -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI&campaign_id=44"
```

Common Errors

Error	Meaning
`missing_api_key`	No API key was supplied in the query string, `X-API-Key`, or bearer token.
`invalid_api_key`	The supplied key does not match the tenant or global API key.
`tenant_required`	A tenant code is required for tenant-scoped writes or tenant-key reads.
`read_only_api_key`	The key can read data but cannot create, update, or delete objects.
`missing_required_field`	A required create field is missing.

Revision #20
Created 2026-06-06 07:32:28 UTC by Admin
Updated 2026-10-18 11:07:32 UTC by Admin