

Campaign Number

The **Campaign Number** object is supported by the MiRTA PBX OpenAPI endpoint. This object is tenant-scoped. Tenant API keys must include `tenant=CANISTRACCI`; writes require a writable API key.

Object Summary

Property	Value
Object	<code>campaignnumber</code>
Primary path	<code>/campaignnumbers</code>
ID field	<code>cn_id</code>
Label field	<code>cn_number</code>
Primary source table	<code>cn_campaignnumbers</code>
Required on create	<code>cn_ca_id</code> , <code>cn_number</code>
Path aliases	<code>/campaignnumber</code> , <code>/campaignnumbers</code> , <code>/campaign_number</code> , <code>/campaign_numbers</code>

Endpoint Patterns

Action	Example pattern
List	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI</code>
Get by ID	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI</code>
Create	<code>POST</code> <code>https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI</code>
Update	<code>PATCH</code> <code>https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI</code>
Delete	<code>DELETE</code> <code>https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI</code>

Accepted Field Aliases

Request field	Source field
campaign_id	cn_ca_id
number	cn_number
description	cn_description
disposition	cn_disposition
attempts	cn_attempts
lastattempt	cn_lastattempt
billsec	cn_billsec

Examples

List Campaign Numbers

Returns the campaign numbers visible to the key and scope.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI"
```

Get Campaign Number

Reads one object by its internal ID.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI"
```

Create Campaign Number

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \  
  -H "X-API-Key: TENANT_API_KEY" \  
  {  
    "number": 123456789,  
    "description": "Test Campaign Number",  
    "disposition": "Test Disposition",  
    "attempts": 1,  
    "lastattempt": "2023-01-01T12:00:00Z",  
    "billsec": 10  
  }
```

```
-H "Content-Type: application/json" \  
-d '{  
  "campaign_id": 44,  
  "number": "+15557654321",  
  "description": "Docs API campaign target"  
}' \  
"https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI"
```

Edit Campaign Number

Updates only the supplied fields.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "disposition": "CALLBACK",  
    "attempts": 1  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI"
```

Delete Campaign Number

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \  
  -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers/OBJECT_ID?tenant=CANISTRACCI"
```

List Campaign Numbers for One Campaign

Filters the list by the parent campaign ID. The aliases `caid` and `cn_ca_id` are also accepted.

```
curl -X GET \  
  -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/campaignnumbers?tenant=CANISTRACCI&campaign_id=44"
```

Common Errors

Error	Meaning
<code>missing_api_key</code>	No API key was supplied in the query string, <code>X-API-Key</code> , or bearer token.
<code>invalid_api_key</code>	The supplied key does not match the tenant or global API key.
<code>tenant_required</code>	A tenant code is required for tenant-scoped writes or tenant-key reads.
<code>read_only_api_key</code>	The key can read data but cannot create, update, or delete objects.
<code>missing_required_field</code>	A required create field is missing.

Revision #20

Created 2026-06-06 07:32:28 UTC by Admin

Updated 2026-10-18 11:07:32 UTC by Admin