

Campaign

The **Campaign** object is supported by the MiRTA PBX OpenAPI endpoint. This object is tenant-scoped. Tenant API keys must include `tenant=CANISTRACCI`; writes require a writable API key.

Object Summary

Property	Value
Object	<code>campaign</code>
Primary path	<code>/campaigns</code>
ID field	<code>ca_id</code>
Label field	<code>ca_name</code>
Primary source table	<code>ca_campaigns</code>
Required on create	<code>ca_name</code>
Path aliases	<code>/campaign</code> , <code>/campaigns</code>

Endpoint Patterns

Action	Example pattern
List	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/campaigns?tenant=CANISTRACCI</code>
Get by ID	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI</code>
Create	<code>POST</code> <code>https://pbx.example.com/pbx/openapi.php/campaigns?tenant=CANISTRACCI</code>
Update	<code>PATCH</code> <code>https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI</code>
Delete	<code>DELETE</code> <code>https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI</code>

Accepted Field Aliases

Request field	Source field
name	ca_name
type	ca_type
tech	ca_tech
datestart	ca_datestart
dateend	ca_dateend
condition_id	ca_co_id
callerid	ca_callerid
calleridname	ca_calleridname
state	ca_state
queue_id	ca_qu_id
message	ca_message
confirmmessage_id	ca_confirmmessage_me_id

Destination Fields

Destination fields accept one destination string or an array of destination strings such as `EXT-100`, `VOICEMAIL-100`, or another supported destination type and ID pair.

Destination type	Accepted aliases
CAMPAIGN-ONCONNECT	onconnect, on_connect
CAMPAIGN-DONOTCALL	donotcall, do_not_call

Examples

List Campaigns

Returns the campaigns visible to the key and scope.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/campaigns?tenant=CANISTRACCI"
```

Get Campaign

Reads one object by its internal ID.

```
curl -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI"
```

Create Campaign

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \
  -H "X-API-Key: TENANT_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "Docs API Campaign",
    "type": "VOICE",
    "tech": "PJSIP",
    "callerid": "+15551234567",
    "state": "PAUSED"
  }' \
  "https://pbx.example.com/pbx/openapi.php/campaigns?tenant=CANISTRACCI"
```

Edit Campaign

Updates only the supplied fields.

```
curl -X PATCH \
  -H "X-API-Key: TENANT_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "state": "ACTIVE"
  }' \
  "https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI"
```

Delete Campaign

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \  
  -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI"
```

Campaign ONCONNECT Destination

Updates the `CAMPAIGN-ONCONNECT` destination. The same value can also be sent inside a `destinations` object.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "onconnect": [  
      "EXT-100"  
    ]  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI"
```

Campaign DONOTCALL Destination

Updates the `CAMPAIGN-DONOTCALL` destination. The same value can also be sent inside a `destinations` object.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "donotcall": [  
      22  
    ]  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI"
```

Campaign Binary File References

Adds binary or fax-related files to the campaign. Use complete base64 data in production integrations.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "binary_files": [  
      {  
        "name": "docs-script.txt",  
        "data_base64": "VGhpcyBpcyBhIGRvY3VtZW50YXRpb24gZXhhbXBsZS4="   
      }  
    ]  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/campaigns/OBJECT_ID?tenant=CANISTRACCI"
```

Common Errors

Error	Meaning
missing_api_key	No API key was supplied in the query string, X-API-Key , or bearer token.
invalid_api_key	The supplied key does not match the tenant or global API key.
tenant_required	A tenant code is required for tenant-scoped writes or tenant-key reads.
read_only_api_key	The key can read data but cannot create, update, or delete objects.
missing_required_field	A required create field is missing.