

Hunt List

The **Hunt List** object is supported by the MiRTA PBX OpenAPI endpoint. This object is tenant-scoped. Tenant API keys must include `tenant=CANISTRACCI`; writes require a writable API key.

Object Summary

Property	Value
Object	<code>huntlist</code>
Primary path	<code>/huntlists</code>
ID field	<code>hu_id</code>
Label field	<code>hu_name</code>
Primary source table	<code>hu_huntlists</code>
Required on create	<code>hu_name</code>
Path aliases	<code>/huntlists</code>

Endpoint Patterns

Action	Example pattern
List	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/huntlists?tenant=CANISTRACCI</code>
Get by ID	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/huntlists/OBJECT_ID?tenant=CANISTRACCI</code>
Create	<code>POST</code> <code>https://pbx.example.com/pbx/openapi.php/huntlists?tenant=CANISTRACCI</code>
Update	<code>PATCH</code> <code>https://pbx.example.com/pbx/openapi.php/huntlists/OBJECT_ID?tenant=CANISTRACCI</code>
Delete	<code>DELETE</code> <code>https://pbx.example.com/pbx/openapi.php/huntlists/OBJECT_ID?tenant=CANISTRACCI</code>

Accepted Field Aliases

Request field	Source field
name	hu_name
number	hu_number
type	hu_type
ringtime	hu_ringtime

Destination Fields

Destination fields accept one destination string or an array of destination strings such as `EXT-100`, `VOICEMAIL-100`, or another supported destination type and ID pair.

Destination type	Accepted aliases
HUNTLIST	extensions, members, huntlist
HUNTLIST-TIMEOUT	timeout, huntlist_timeout

Examples

List Hunt Lists

Returns the hunt lists visible to the key and scope.

```
curl -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/huntlists?tenant=CANISTRACCI"
```

Get Hunt List

Reads one object by its internal ID.

```
curl -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/huntlists/OBJECT_ID?tenant=CANISTRACCI"
```

Create Hunt List

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "name": "Docs API Hunt List",  
    "number": "820",  
    "type": "RINGALL",  
    "ringtime": 20  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/huntlists?tenant=CANISTRACCI"
```

Edit Hunt List

Updates only the supplied fields.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "ringtime": 25  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/huntlists/OBJECT_ID?tenant=CANISTRACCI"
```

Delete Hunt List

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \  
  -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/huntlists/OBJECT_ID?tenant=CANISTRACCI"
```

Hunt List Destination

Updates the `HUNTLIST` destination. The same value can also be sent inside a `destinations` object.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "extensions": [  
      "EXT-100"  
    ]  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/huntlists/OBJECT_ID?tenant=CANISTRACCI"
```

Hunt List TIMEOUT Destination

Updates the `HUNTLIST-TIMEOUT` destination. The same value can also be sent inside a `destinations` object.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "timeout": [  
      "EXT-100"  
    ]  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/huntlists/OBJECT_ID?tenant=CANISTRACCI"
```

Common Errors

Error	Meaning
<code>missing_api_key</code>	No API key was supplied in the query string, <code>X-API-Key</code> , or bearer token.
<code>invalid_api_key</code>	The supplied key does not match the tenant or global API key.
<code>tenant_required</code>	A tenant code is required for tenant-scoped writes or tenant-key reads.
<code>read_only_api_key</code>	The key can read data but cannot create, update, or delete objects.

Error	Meaning
<code>missing_required_field</code>	A required create field is missing.

Revision #18
Created 2026-06-06 07:32:09 UTC by Admin
Updated 2026-07-03 15:49:07 UTC by Admin