

Provisioning Phone

The **Provisioning Phone** object is supported by the MiRTA PBX OpenAPI endpoint. This object is tenant-scoped. Tenant API keys must include `tenant=CANISTRACCI`; writes require a writable API key.

Object Summary

Property	Value
Object	<code>provisioningphone</code>
Primary path	<code>/provisioningphones</code>
ID field	<code>ph_id</code>
Label field	<code>ph_name</code>
Primary source table	<code>ph_phones</code>
Required on create	<code>ph_name</code> , <code>ph_mac</code>
Path aliases	<code>/phone</code> , <code>/phones</code> , <code>/provisioningphones</code> , <code>/provisioning_phones</code> , <code>/provisioning_phone</code>

Endpoint Patterns

Action	Example pattern
List	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/provisioningphones?tenant=CANISTRACCI</code>
Get by ID	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/provisioningphones/OBJECT_ID?tenant=CANISTRACCI</code>
Create	<code>POST</code> <code>https://pbx.example.com/pbx/openapi.php/provisioningphones?tenant=CANISTRACCI</code>
Update	<code>PATCH</code> <code>https://pbx.example.com/pbx/openapi.php/provisioningphones/OBJECT_ID?tenant=CANISTRACCI</code>
Delete	<code>DELETE</code> <code>https://pbx.example.com/pbx/openapi.php/provisioningphones/OBJECT_ID?tenant=CANISTRACCI</code>

Accepted Field Aliases

Request field	Source field
name	ph_name
mac	ph_mac
model_id	ph_pm_id
password	ph_password
filename	ph_filename
http_user	ph_http_user
http_password	ph_http_password

Examples

List Provisioning Phones

Returns the provisioning phones visible to the key and scope.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/provisioningphones?tenant=CANISTRACCI"
```

Get Provisioning Phone

Reads one object by its internal ID.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/provisioningphones/OBJECT_ID?tenant=CANISTRACCI"
```

Create Provisioning Phone

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \  
  -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/provisioningphones?tenant=CANISTRACCI"
```

```
-H "Content-Type: application/json" \  
-d '{  
  "name": "Docs API Desk Phone",  
  "mac": "001122334455",  
  "model_id": 1,  
  "filename": "docs-api-001122334455.cfg"  
}' \  
"https://pbx.example.com/pbx/openapi.php/provisioningphones?tenant=CANISTRACCI"
```

Edit Provisioning Phone

Updates only the supplied fields.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "http_user": "phone-user",  
    "http_password": "change-this-password"  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/provisioningphones/OBJECT_ID?tenant=CANISTRACCI"
```

Delete Provisioning Phone

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \  
  -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/provisioningphones/OBJECT_ID?tenant=CANISTRACCI"
```

Common Errors

Error	Meaning
<code>missing_api_key</code>	No API key was supplied in the query string, <code>X-API-Key</code> , or bearer token.
<code>invalid_api_key</code>	The supplied key does not match the tenant or global API key.

Error	Meaning
<code>tenant_required</code>	A tenant code is required for tenant-scoped writes or tenant-key reads.
<code>read_only_api_key</code>	The key can read data but cannot create, update, or delete objects.
<code>missing_required_field</code>	A required create field is missing.

Revision #18
Created 2026-06-06 07:32:34 UTC by Admin
Updated 2026-07-03 15:49:17 UTC by Admin