

Setting

The **Setting** object is supported by the MiRTA PBX OpenAPI endpoint. This object is normally tenant-scoped. With a global API key, use `global=1` to manage the shared/global record set. Tenant writes still require `tenant=CANISTRACCI`.

Object Summary

Property	Value
Object	<code>setting</code>
Primary path	<code>/settings</code>
ID field	<code>se_id</code>
Label field	<code>se_code</code>
Primary source table	<code>se_settings</code>
Required on create	<code>se_code</code>
Path aliases	<code>/settings</code>

Endpoint Patterns

Action	Example pattern
List	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/settings?tenant=CANISTRACCI</code>
Get by ID	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/settings/OBJECT_ID?tenant=CANISTRACCI</code>
Create	<code>POST</code> <code>https://pbx.example.com/pbx/openapi.php/settings?tenant=CANISTRACCI</code>
Update	<code>PATCH</code> <code>https://pbx.example.com/pbx/openapi.php/settings/OBJECT_ID?tenant=CANISTRACCI</code>
Delete	<code>DELETE</code> <code>https://pbx.example.com/pbx/openapi.php/settings/OBJECT_ID?tenant=CANISTRACCI</code>

Accepted Field Aliases

Request field	Source field
<code>code</code>	<code>se_code</code>
<code>value</code>	<code>se_value</code>

Examples

List Settings

Returns the settings visible to the key and scope.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/settings?tenant=CANISTRACCI"
```

Get Setting

Reads one object by its internal ID.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/settings/OBJECT_ID?tenant=CANISTRACCI"
```

Create Setting

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "code": "API_DOCS_EXAMPLE",  
    "value": "enabled"  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/settings?tenant=CANISTRACCI"
```

Edit Setting

Updates only the supplied fields.

```
curl -X PATCH \
  -H "X-API-Key: TENANT_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "value": "disabled"
  }' \
  "https://pbx.example.com/pbx/openapi.php/settings/OBJECT_ID?tenant=CANISTRACCI"
```

Delete Setting

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \
  -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/settings/OBJECT_ID?tenant=CANISTRACCI"
```

List Global Settings

Uses the shared/global record set for object types that support global rows.

```
curl -H "X-API-Key: GLOBAL_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/settings?global=1"
```

Common Errors

Error	Meaning
missing_api_key	No API key was supplied in the query string, <code>X-API-Key</code> , or bearer token.
invalid_api_key	The supplied key does not match the tenant or global API key.
tenant_required	A tenant code is required for tenant-scoped writes or tenant-key reads.

Error	Meaning
<code>read_only_api_key</code>	The key can read data but cannot create, update, or delete objects.
<code>missing_required_field</code>	A required create field is missing.

Revision #18
Created 2026-06-06 07:32:14 UTC by Admin
Updated 2026-07-03 15:49:09 UTC by Admin