

Tenant Variable

The **Tenant Variable** object is supported by the MiRTA PBX OpenAPI endpoint. This object is tenant-scoped. Tenant API keys must include `tenant=CANISTRACCI`; writes require a writable API key.

Object Summary

Property	Value
Object	<code>tenantvariable</code>
Primary path	<code>/tenantvariables</code>
ID field	<code>tv_id</code>
Label field	<code>tv_value</code>
Primary source table	<code>tv_tenantvariables</code>
Required on create	<code>tv_al_id</code>
Path aliases	<code>/variable</code> , <code>/variables</code> , <code>/tenantvariable</code> , <code>/tenantvariables</code> , <code>/tenant_variable</code> , <code>/tenant_variables</code>

Endpoint Patterns

Action	Example pattern
List	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/tenantvariables?tenant=CANISTRACCI</code>
Get by ID	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/tenantvariables/OBJECT_ID?tenant=CANISTRACCI</code>
Create	<code>POST</code> <code>https://pbx.example.com/pbx/openapi.php/tenantvariables?tenant=CANISTRACCI</code>
Update	<code>PATCH</code> <code>https://pbx.example.com/pbx/openapi.php/tenantvariables/OBJECT_ID?tenant=CANISTRACCI</code>
Delete	<code>DELETE</code> <code>https://pbx.example.com/pbx/openapi.php/tenantvariables/OBJECT_ID?tenant=CANISTRACCI</code>

Accepted Field Aliases

Request field	Source field
<code>variable_id</code>	<code>tv_al_id</code>
<code>value</code>	<code>tv_value</code>
<code>comment</code>	<code>tv_comment</code>
<code>locked</code>	<code>tv_locked</code>

Examples

List Tenant Variables

Returns the tenant variables visible to the key and scope.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/tenantvariables?tenant=CANISTRACCI"
```

Get Tenant Variable

Reads one object by its internal ID.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/tenantvariables/OBJECT_ID?tenant=CANISTRACCI"
```

Create Tenant Variable

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "variable_id": 1,  
    "value": "docs-value",
```

```
"comment": "Docs API variable value"
}' \
"https://pbx.example.com/pbx/openapi.php/tenantvariables?tenant=CANISTRACCI"
```

Edit Tenant Variable

Updates only the supplied fields.

```
curl -X PATCH \
  -H "X-API-Key: TENANT_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "value": "docs-updated-value"
  }' \
  "https://pbx.example.com/pbx/openapi.php/tenantvariables/OBJECT_ID?tenant=CANISTRACCI"
```

Delete Tenant Variable

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \
  -H "X-API-Key: TENANT_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/tenantvariables/OBJECT_ID?tenant=CANISTRACCI"
```

Common Errors

Error	Meaning
<code>missing_api_key</code>	No API key was supplied in the query string, <code>X-API-Key</code> , or bearer token.
<code>invalid_api_key</code>	The supplied key does not match the tenant or global API key.
<code>tenant_required</code>	A tenant code is required for tenant-scoped writes or tenant-key reads.
<code>read_only_api_key</code>	The key can read data but cannot create, update, or delete objects.
<code>missing_required_field</code>	A required create field is missing.

Revision #18
Created 2026-06-06 07:32:22 UTC by Admin
Updated 2026-07-03 15:49:12 UTC by Admin