

Tenant

The **Tenant** object is supported by the MiRTA PBX OpenAPI endpoint. This object is managed at system scope and requires a global API key.

Object Summary

Property	Value
Object	tenant
Primary path	/tenants
ID field	te_id
Label field	te_name
Primary source table	te_tenants
Required on create	te_name, te_code
Path aliases	/tenants

Endpoint Patterns

Action	Example pattern
List	GET https://pbx.example.com/pbx/openapi.php/tenants
Get by ID	GET https://pbx.example.com/pbx/openapi.php/tenants/OBJECT_ID
Create	POST https://pbx.example.com/pbx/openapi.php/tenants
Update	PATCH https://pbx.example.com/pbx/openapi.php/tenants/OBJECT_ID
Delete	DELETE https://pbx.example.com/pbx/openapi.php/tenants/OBJECT_ID

Accepted Field Aliases

Request field	Source field
name	te_name
code	te_code
billingcode	te_billingcode
billing_code	te_billingcode
timezone	te_timezone
routing_profile_id	te_rp_id
campaign_routing_profile_id	te_campaign_rp_id
fax_routing_profile_id	te_fax_rp_id

Examples

List Tenants

Returns the tenants visible to the key and scope.

```
curl -H "X-API-Key: GLOBAL_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/tenants"
```

Get Tenant

Reads one object by its internal ID.

```
curl -H "X-API-Key: GLOBAL_API_KEY" \
  "https://pbx.example.com/pbx/openapi.php/tenants/OBJECT_ID"
```

Create Tenant

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \
  -H "X-API-Key: GLOBAL_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "Docs API Tenant",
```

```
"code": "DOCSAPI",
"timezone": "Europe/Rome"
}' \
"https://pbx.example.com/pbx/openapi.php/tenants"
```

Edit Tenant

Updates only the supplied fields.

```
curl -X PATCH \
-H "X-API-Key: GLOBAL_API_KEY" \
-H "Content-Type: application/json" \
-d '{
  "routing_profile_id": 3,
  "te_payment_type": "Post Paid"
}' \
"https://pbx.example.com/pbx/openapi.php/tenants/OBJECT_ID"
```

Delete Tenant

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \
-H "X-API-Key: GLOBAL_API_KEY" \
"https://pbx.example.com/pbx/openapi.php/tenants/OBJECT_ID"
```

Common Errors

Error	Meaning
<code>missing_api_key</code>	No API key was supplied in the query string, <code>X-API-Key</code> , or bearer token.
<code>invalid_api_key</code>	The supplied key does not match the tenant or global API key.
<code>tenant_required</code>	A tenant code is required for tenant-scoped writes or tenant-key reads.
<code>read_only_api_key</code>	The key can read data but cannot create, update, or delete objects.

Error	Meaning
missing_required_field	A required create field is missing.

Revision #17
Created 2026-06-06 07:31:58 UTC by Admin
Updated 2026-07-03 15:49:02 UTC by Admin