

User Profile

The **User Profile** object is supported by the MiRTA PBX OpenAPI endpoint. This object is managed at system scope and requires a global API key.

Object Summary

Property	Value
Object	userprofile
Primary path	/userprofiles
ID field	up_id
Label field	up_name
Primary source table	up_userprofiles
Required on create	up_name
Path aliases	/userprofile, /userprofiles, /user_profile, /user_profiles

Endpoint Patterns

Action	Example pattern
List	GET https://pbx.example.com/pbx/openapi.php/userprofiles
Get by ID	GET https://pbx.example.com/pbx/openapi.php/userprofiles/OBJECT_ID
Create	POST https://pbx.example.com/pbx/openapi.php/userprofiles
Update	PATCH https://pbx.example.com/pbx/openapi.php/userprofiles/OBJECT_ID
Delete	DELETE https://pbx.example.com/pbx/openapi.php/userprofiles/OBJECT_ID

Accepted Field Aliases

Request field	Source field
name	up_name
description	up_description
reserved	up_reserved
userpanel	up_userpanel
user_panel	up_userpanel
extension_user_profile	up_userpanel

Examples

List User Profiles

Returns the user profiles visible to the key and scope.

```
curl -H "X-API-Key: GLOBAL_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/userprofiles"
```

Get User Profile

Reads one object by its internal ID.

```
curl -H "X-API-Key: GLOBAL_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/userprofiles/OBJECT_ID"
```

Create User Profile

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \  
  -H "X-API-Key: GLOBAL_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{
```

```
"name": "Docs API Profile",
"description": "Documentation profile",
"user_panel": "yes"
}' \
"https://pbx.example.com/pbx/openapi.php/userprofiles"
```

Edit User Profile

Updates only the supplied fields.

```
curl -X PATCH \
-H "X-API-Key: GLOBAL_API_KEY" \
-H "Content-Type: application/json" \
-d '{
  "description": "Updated documentation profile"
}' \
"https://pbx.example.com/pbx/openapi.php/userprofiles/OBJECT_ID"
```

Delete User Profile

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \
-H "X-API-Key: GLOBAL_API_KEY" \
"https://pbx.example.com/pbx/openapi.php/userprofiles/OBJECT_ID"
```

User Profile Privileges

Replaces the profile privilege list. Privilege IDs must exist in the system privilege table.

```
curl -X PATCH \
-H "X-API-Key: GLOBAL_API_KEY" \
-H "Content-Type: application/json" \
-d '{
  "privileges": [
    {
      "id": 1,
```

```
    "param1": "read"
  },
  {
    "id": 2,
    "param1": "write"
  }
]
}' \

"https://pbx.example.com/pbx/openapi.php/userprofiles/OBJECT_ID"
```

Common Errors

Error	Meaning
missing_api_key	No API key was supplied in the query string, <code>X-API-Key</code> , or bearer token.
invalid_api_key	The supplied key does not match the tenant or global API key.
tenant_required	A tenant code is required for tenant-scoped writes or tenant-key reads.
read_only_api_key	The key can read data but cannot create, update, or delete objects.
missing_required_field	A required create field is missing.

Revision #17

Created 2026-06-06 07:32:00 UTC by Admin

Updated 2026-07-03 15:49:03 UTC by Admin