

Voicemail

The **Voicemail** object is supported by the MiRTA PBX OpenAPI endpoint. This object is tenant-scoped. Tenant API keys must include `tenant=CANISTRACCI`; writes require a writable API key.

Object Summary

Property	Value
Object	<code>voicemail</code>
Primary path	<code>/voicemails</code>
ID field	<code>uniqueid</code>
Label field	<code>mailbox</code>
Primary source table	<code>voicemail</code>
Required on create	<code>mailbox</code>
Path aliases	<code>/voicemails</code>

Endpoint Patterns

Action	Example pattern
List	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/voicemails?tenant=CANISTRACCI</code>
Get by ID	<code>GET</code> <code>https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI</code>
Create	<code>POST</code> <code>https://pbx.example.com/pbx/openapi.php/voicemails?tenant=CANISTRACCI</code>
Update	<code>PATCH</code> <code>https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI</code>
Delete	<code>DELETE</code> <code>https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI</code>

Accepted Field Aliases

Request field	Source field
<code>name</code>	<code>fullname</code>
<code>number</code>	<code>mailbox</code>

Destination Fields

Destination fields accept one destination string or an array of destination strings such as `EXT-100`, `VOICEMAIL-100`, or another supported destination type and ID pair.

Destination type	Accepted aliases
<code>VOICEMAIL-OPERATOR</code>	<code>operator</code> , <code>voicemail_operator</code>
<code>VOICEMAIL-FOLLOW</code>	<code>follow</code> , <code>voicemail_follow</code>
<code>VOICEMAIL-BROADCAST</code>	<code>broadcast</code> , <code>voicemail_broadcast</code>

Examples

List Voicemails

Returns the voicemails visible to the key and scope.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/voicemails?tenant=CANISTRACCI"
```

Get Voicemail

Reads one object by its internal ID.

```
curl -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI"
```

Create Voicemail

Creates a new object. Use the short aliases shown above or the source field names.

```
curl -X POST \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "number": "240",  
    "name": "Docs API Mailbox",  
    "email": "voicemail@example.com",  
    "password": "1234"  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/voicemails?tenant=CANISTRACCI"
```

Edit Voicemail

Updates only the supplied fields.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "name": "Docs API Mailbox Updated",  
    "email": "voicemail-updated@example.com"  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI"
```

Delete Voicemail

Deletes the object. Check references before deleting configuration used by routing or reporting.

```
curl -X DELETE \  
  -H "X-API-Key: TENANT_API_KEY" \  
  "https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI"
```

Voicemail OPERATOR Destination

Updates the `VOICEMAIL-OPERATOR` destination. The same value can also be sent inside a `destinations` object.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "operator": [  
      "EXT-100"  
    ]  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI"
```

Voicemail FOLLOW Destination

Updates the `VOICEMAIL-FOLLOW` destination. The same value can also be sent inside a `destinations` object.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "follow": [  
      "EXT-100"  
    ]  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI"
```

Voicemail BROADCAST Destination

Updates the `VOICEMAIL-BROADCAST` destination. The same value can also be sent inside a `destinations` object.

```
curl -X PATCH \  
  -H "X-API-Key: TENANT_API_KEY" \  
  -H "Content-Type: application/json" \  
  -d '{  
    "broadcast": [  
      "EXT-100"  
    ]  
  }' \  
  "https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI"
```

"EXT-100"

]

}' \

"https://pbx.example.com/pbx/openapi.php/voicemails/OBJECT_ID?tenant=CANISTRACCI"

Common Errors

Error	Meaning
missing_api_key	No API key was supplied in the query string, <code>X-API-Key</code> , or bearer token.
invalid_api_key	The supplied key does not match the tenant or global API key.
tenant_required	A tenant code is required for tenant-scoped writes or tenant-key reads.
read_only_api_key	The key can read data but cannot create, update, or delete objects.
missing_required_field	A required create field is missing.

Revision #18

Created 2026-06-06 07:32:04 UTC by Admin

Updated 2026-07-03 15:49:05 UTC by Admin