

Settings

Settings administration tasks.

- [Overview](#)
- [Upgrade and Version](#)
- [Dialing and Internationalization](#)
- [Security and Access](#)
- [Backups](#)

Overview

Use **Admin > Settings** to manage global MiRTA PBX behavior. These settings are system-wide, so changes can affect multiple tenants, integrations, storage backends, and background jobs.

Working with Admin Settings

Action	Description
Open	Open Admin > Settings from the Global Administration menu.
Review	Work section by section. Global changes should be checked against tenants, nodes, storage services, and integrations that depend on them.
Save	Use Save at the bottom of the form to apply changes. Some changes, such as upgrade, housekeeping, media-file, or test actions, run their own action from the relevant section.
Custom extension usernames	Enable Allow extensions with custom usernames in the Security section when SIP extensions must use usernames that do not follow the generated tenant-code format.

Version

Version

Software in use: 4.24.3

Check for upgradesDetailsUpgrade

Database schema: 2186

Run Housekeeping

Database upgrade: Not Running

Version section of Admin Settings.

Use this section to check the installed software version, database schema status, available upgrades, and maintenance actions.

Field or option	Purpose
-----------------	---------

Software in use	Sets the Software in use value for Version.
Database schema	Sets the Database schema value for Version.
Database upgrade (Select)	Selects the Database upgrade behavior for Version.

Internationalization

Internationalization

Currency:

Internationalization section of Admin Settings.

Use this section for global locale defaults such as the system currency.

Field or option	Purpose
Currency	Sets the Currency value for Internationalization.

Dialing

Dialing

International prefix:

Trunk prefix:

Country code:

Voice messages language:

Inbound CallerID Modifications:

No Modifications

Allowed Outbound Digits:

DID matching:

At least Area Code + Number

☐ Always route calls to provider

☐ Force selection of Caller ID

☐ Force selection of Emergency Caller ID

☒ Force feature codes to start by # or *

☒ Replace + with the international prefix (outbound)

☐ Allow Regex in DID number

Dialing section of Admin Settings.

Use this section for global dialing defaults, caller ID handling, DID matching, and feature-code restrictions.

Field or option	Purpose
International prefix	Sets the International prefix value for Dialing.
Trunk prefix	Sets the Trunk prefix value for Dialing.
Country code	Country Code: You can specify the country code, like 39, so any call using the international prefix, but the country code, will not be treated as international
Voice messages language (Select)	Language: This option controls the selection of the language in Asterisk embedded message playback
Inbound CallerID Modifications (Select)	Selects the Inbound CallerID Modifications behavior for Dialing.
Allowed Outbound Digits	Sets the Allowed Outbound Digits value for Dialing.
DID matching (Select)	Allow DID matching for number only: When a DID is searched in the system, at least a match for areacode + number is required, when a provider sends only the number part.
Always route calls to provider (Checkbox)	Always route calls to provider: Even if the number dialed is defined on the PBX, route it to the provider.
Force selection of Caller ID (Checkbox)	Force selection of Caller ID: Force selection of a numeric Caller ID number, hide selection of ANONYMOUS and WITHHELD from extensions Caller ID selection
Force selection of Emergency Caller ID (Checkbox)	Force selection of Emergency Caller ID: Force selection of an emergency Caller ID. You can set it at tenant or extension level
Force feature codes to start by # or * (Checkbox)	Force feature codes to start either by # or *: By enabling this, a feature code must start by * or # otherwise you can use anything as feature code
Replace + with the international prefix (outbound) (Checkbox)	Replace + with the international prefix (outbound): By enabling this, when dialing out, it replaces the + with the international prefix
Allow Regex in DID number (Checkbox)	Allow Regex in DID number: Allow to use a regex for the number in the DID page. Be warned, a wrong regex can stop all calls

License

License

License key:

License code: demo

Max tenants: 9999999

Max peers: 999999999

Max nodes: 999999999

License expires: 2027-01-12

Maintenance and support expires: 2027-01-12

Licensed domain: mirtapbx.com!213.133.102.85!88.198.206.51!88.99.39.9!138.201.140.216!95.217.87.47!195.201.225.82

License section of Admin Settings.

Use this section to store the system license key.

Field or option	Purpose
License key	Sets the License key value for License.

API Interface

API Interface

General API Key:

General Read Only API Key:

Cache Asterisk results (seconds):

API Interface section of Admin Settings.

Use this section to manage global API credentials and API-side Asterisk result caching.

Field or option	Purpose
General API Key	Sets the General API Key value for API Interface.
General Read Only API Key	Sets the General Read Only API Key value for API Interface.
Cache Asterisk results (seconds)	Cache Asterisk results (seconds): API calls can put heavy load on Asterisk, so you can specify a time in seconds to retain results and use as cache

DB Data Retention

DB Data Retention

Advanced Call Detail info days:	5
Advanced Call Detail media (pcap and graphs) days:	5
Call history days:	365
SMS history days:	90
SMS retention days:	30
Call Steps (CEL) history days:	5
Queue history days:	90
Queue history days (informative data):	
Provisioning and event history days:	5
Provisioning feedback days:	5
Activity log history days:	365
Recording holding days:	3650
Recording metadata holding days:	180
Voicemail message holding days:	3650
Fax holding days:	3650
IVR log holding days:	90
Conference log holding days:	90
Process log holding days:	5
Reports default holding days:	90

Admin Settings DB Data Retention section with Recording metadata holding days shown with fictional documentation data.

Use this section to define how long operational data remains in the database before cleanup. Recording metadata can have its own retention period, or it can follow the recording retention value when left empty.

Field or option	Purpose
Advanced Call Detail info days	Advanced Call Detail info days: Sets the retention period for the Voipmonitor CDR data. You can access them from the call history, using the disposition link
Advanced Call Detail media (pcap and graphs) days	Advanced Call Detail media (pcap and graphs) days: Sets the retention period from the Voipmonitor pcap and graphs
Call history days	Call history days: Sets the retention days for call history, both Simple Call History and Complete Call History
SMS history days	SMS history days: Sets the retention days for SMS History
SMS retention days	SMS retention days: Sets the number of days to keep trying to send an SMS
Call Steps (CEL) history days	Call Steps (CEL) history days: Sets the retention days for the Call Steps data and CEL table
Queue history days	Queue history days: Sets the retention days for the queue history logs
Queue history days (informative data)	Queue history days (informative data): Sets the retention days for the informative events of the queue history, like NO FREE AGENTS and NOT THE RIGHT TIME
Provisioning and event history days	Sets the Provisioning and event history days value for DB Data Retention.
Provisioning feedback days	Sets the Provisioning feedback days value for DB Data Retention.
Activity log history days	Sets the Activity log history days value for DB Data Retention.
Recording holding days	Sets the Recording holding days value for DB Data Retention.
Recording metadata holding days	Sets how many days recording metadata such as transcripts, summaries, sentiment analysis, and AI analysis details remain in rm_recordingmetadatas. Leave empty to follow Recording holding days.
Voicemail message holding days	Sets the Voicemail message holding days value for DB Data Retention.
Fax holding days	Sets the Fax holding days value for DB Data Retention.
IVR log holding days	Sets the IVR log holding days value for DB Data Retention.
Conference log holding days	Sets the Conference log holding days value for DB Data Retention.
Process log holding days	Sets the Process log holding days value for DB Data Retention.
Reports default holding days	Sets the Reports default holding days value for DB Data Retention.

Recording

Recording

Storage type: SFTP Server

Host: *****

User: *****

Password: *****

Directory: *****

Recording name: Uniqueid

Recording format: Uncompressed 16-bit PCM audio

Recording conversion: No conversion

Process recording at call end: Yes

Batch recording processing: Every 1 minute

Batch recording dynamic scaling: No

Batch recording matching: Aggressive

Unmatched recording: Delete

Multi channel recording: No

Stereo recording: No

Early recording: No

Process all recording legs: Yes

☐ Remove recordings on database expiration

Recording section of Admin Settings.

Use this section for global call-recording storage, naming, conversion, upload, and post-processing behavior.

Field or option	Purpose
Storage type (Select)	Storage type: Sets the storage backend for call recordings. Data retention limits are applied only to Database backend (for now).

Field or option	Purpose
JSON Service Account key (Text area)	Sets the JSON Service Account key value for Recording.
Host (Select)	Host: If your FTP server is not using the standard port 21, you can configure the desired port using a host:port syntax.
User	Sets the User value for Recording.
Password	Sets the Password value for Recording.
Directory	Sets the Directory value for Recording.
Recording name (Select)	Recording name: You can choose the name of the recording. When using a file based recording storage, it is important to add the Random prefix to avoid multiple legs recording to be overwritten
Recording format (Select)	Recording format: Sets the recording format using while capturing the audio during the call. There were multiple reports about audio corruption when using MS GSM audio
Recording conversion (Select)	Recording conversion: After the recording has been capturing and before uploading to the choosen storage, convert to a different format.
Process recording at call end (Select)	Process recording at call end: Sets if to process recording at call end. When using process at call end, the recording is available immediately after the call ends, but system load average is higher, higher database connection slots are used and the call duration recorded is slightly longer) When doing only batch process, there is a low impact on system load, lower database connection slots are used, but recordings are available after the scheduled time
Batch recording processing (Select)	Batch recording process: Sets when to process recording left on the system. If configured, the system tries to process/upload the call recording when call ends, but in case of transfers, the process/upload of the recording can be delayed and it is processed/uploaded in batch
Batch recording dynamic scaling (Select)	Batch recording dynamic scaling: Starts additional upload processes if there are lots of files to be uploaded
Batch recording matching (Select)	Batch recording matching: A call can be split in several legs and several recordings. Normal matching will upload only recordings belonging to the primary leg. Aggressive matching will upload recording from any leg. It is possible it will be uploaded also recording that has been stopped with a feature code.
Unmatched recording (Select)	Unmatched recording: What has to do with recordings not matching any call unique ID. Usually they are additional recordings generated when call are transfered and can be thrown away because they are duplicates.
Multi channel recording (Select)	Multi channel recording: You can record each party audio in a different file

Field or option	Purpose
Stereo recording (Select)	Stereo recording: The recording will be a stereo media file with each party in a different audio stream
Early recording (Select)	Early recording: The recording will include any audio before the call is bridged.
Process all recording legs (Select)	Process all recording legs: When enabled, all the recording legs are processed regarding email, transcript, summary and sentimental analysis.
Remove recordings on database expiration (Checkbox)	Remove recordings on database expiration: When the recording metadata is removed from the database, the corresponding recording file is deleted. It doesn't work retroactively.

Media Files

Media Files

Storage type: Database

Media Files section of Admin Settings.

Use this section to configure where shared media files are stored.

Field or option	Purpose
Storage type (Select)	Storage type: Sets the storage backend for media files
Host (Select)	Host: If your FTP server is not using the standard port 21, you can configure the desired port using a host:port syntax.
User	Sets the User value for Media Files.
Password	Sets the Password value for Media Files.
Directory	Sets the Directory value for Media Files.

Faxes

Faxes

Storage type: Database

Faxes section of Admin Settings.

Use this section for fax storage and fax file retention behavior.

Field or option	Purpose
Storage type (Select)	Storage type: Sets the storage backend for faxes
Host (Select)	Host: If your FTP server is not using the standard port 21, you can configure the desired port using a host:port syntax.
User	Sets the User value for Faxes.
Password	Sets the Password value for Faxes.
Directory	Sets the Directory value for Faxes.
Remove faxes on database expiration (Checkbox)	Remove faxes on database expiration: When the fax metadata is removed from the database, the corresponding fax file is deleted. It doesn't work retroactively.

Billing

Billing

Dashboard show:

From start of time

▼

Alert email:

Billing section of Admin Settings.

Use this section for billing dashboard visibility and billing alert delivery.

Field or option	Purpose
Dashboard show (Select)	Selects the Dashboard show behavior for Billing.
Alert email	Sets the Alert email value for Billing.

Voice Synthesizer

Voice Synthesizer

Engine:

Google Cloud Text to Speech

▼

Voice:

Italian MALE: Italian - it-IT-Wavenet-C

▼

Download Voices

Voice Engine API password:

Voice Synthesizer section of Admin Settings.

Use this section to configure the text-to-speech engine, voice, service endpoint, and credentials.

Field or option	Purpose
Engine (Select)	Selects the Engine behavior for Voice Synthesizer.
Voice (Select)	Selects the Voice behavior for Voice Synthesizer.
Region (Select)	Selects the Region behavior for Voice Synthesizer.
Full Endpoint URL	Full endpoint URL with instance id like https://api.us-east.speech-to-text.watson.cloud.ibm.com/instances/82baccdd-45ee-46ff-ba1a-3cd23425b3c1/v1/synthesize
Voice Engine API username	Sets the Voice Engine API username value for Voice Synthesizer.
Rate/Pitch	Rate/Pitch parameters: You can control the rate and pitch of the voice to be created by entering them separated by a /, like -11/-70
Voice Engine API password	Sets the Voice Engine API password value for Voice Synthesizer.

Speech to Text

The **Speech to Text** section in **Admin > Settings** configures the global speech-recognition engine and the background jobs that process recorded calls. Tenant-level settings can override some values, but the global configuration is the fallback used by the PBX when a tenant does not define its own engine or credentials.

The screenshots below use fictional values and were captured from the global Admin Settings form without saving changes.

IBM Watson TTS

Speech to Text

Engine: IBM Watson TTS

Full Endpoint URL: https://api.us-south.speech-to-text.watson.cloud.ibm.com/instances/1111

Language: American English Broadband
Download Languages

Speech To Text Engine API username: apikey

Speech To Text Engine API password: fictional-watson-api-key

Transcribe phone call recordings: Every 10 minutes
Docs processing node

☒ Transcribe when recording is uploaded

Minimum call time for transcript: 30

Test speech recognition: Choose File No file chosen
Test

Admin Settings Speech to Text configuration for IBM Watson TTS with fictional documentation values.

Field	Meaning
Engine	Selects IBM Watson as the global Speech to Text provider. The historical label includes TTS, but this panel is used for recognition.
Full Endpoint URL	Watson recognition endpoint, including the service instance and recognize path supplied by IBM.
Language	Watson language and model. Choose the model that matches the spoken language and expected audio bandwidth.
Download Languages	Downloads or refreshes the available Watson language list after the endpoint and credentials are configured.
Speech To Text Engine API username	Watson credential username. Many IBM deployments use <code>apikey</code> as the username.
Speech To Text Engine API password	Watson API key or password.
Transcribe phone call recordings	Schedules batch transcription of recorded calls and selects the node that runs the transcript job.
Transcribe when recording is uploaded	Starts transcript processing immediately after a recording is uploaded, in addition to any scheduled batch processing.
Minimum call time for transcript	Skips recordings shorter than the configured number of seconds.
Test speech recognition	Uploads a WAV file and sends it to the selected engine to verify the global configuration.

Nexiwave

Speech to Text

Engine:

Nexiwave

Language:

English

Speech To Text Engine API username:

docs-nexiwave-user

Speech To Text Engine API password:

fictional-nexiwave-password

☒

Transcribe when recording is uploaded

Minimum call time for transcript:

30

Test speech recognition:

Choose File

No file chosen

Test

Admin Settings Speech to Text configuration for Nexiwave with fictional documentation values.

Field	Meaning
Engine	Selects Nexiwave as the global Speech to Text provider.
Language	Language sent to Nexiwave for recognition.
Speech To Text Engine API username	Nexiwave account username.
Speech To Text Engine API password	Nexiwave password or API secret.
Transcribe when recording is uploaded	When available for the selected engine, starts transcript processing immediately after recording upload.
Minimum call time for transcript	Skips recordings shorter than this duration.
Test speech recognition	Uploads a WAV file and validates the Nexiwave settings.

Google Cloud Speech to Text

Speech to Text

Engine: Google Cloud Speech to Text

Language: English (United States)

Speech To Text Engine API password: fictional-google-api-key

JSON Service Account key:

```
{
  "type": "service_account",
  "project_id": "docs-demo-stt",
  "private_key_id": "fictionalkeyid",
  "private_key": "-----BEGIN PRIVATE KEY-----\nFICTIONAL-KEY\n-----END PRIVATE KEY-----"
}
```

Bucket Name: docs-demo-stt-audio

Profanity filter: Yes

Transcribe phone call recordings: Every 10 minutes

Docs processing node

☒ Transcribe when recording is uploaded

Minimum call time for transcript: 30

Test speech recognition:

Choose File
No file chosen

Test

Admin Settings Speech to Text configuration for Google Cloud Speech to Text with fictional documentation values.

Field	Meaning
Engine	Selects Google Cloud Speech to Text as the global recognition provider.
Language	Google recognition language code. Select the primary language expected in recorded calls.
Speech To Text Engine API password	Google API key used when audio is submitted directly without a storage bucket workflow.
JSON Service Account key	Service account JSON used when audio is staged in Google Cloud Storage. The service account must have access to the configured bucket.
Bucket Name	Google Cloud Storage bucket used to store audio before transcription. The bucket must already exist.
Profanity filter	Controls whether Google attempts to mask profanity in returned transcripts.
Transcribe phone call recordings	Schedules transcript processing for recorded calls and selects the processing node.
Transcribe when recording is uploaded	Starts processing immediately after recording upload.

Field	Meaning
Minimum call time for transcript	Prevents very short recordings from being submitted to Google.
Test speech recognition	Uploads a WAV file to test the Google credentials, language, and bucket/API-key configuration.

AssemblyAI

Speech to Text

Engine:

AssemblyAI

Endpoint server:

api.assemblyai.com

Model:

Universal-3 Pro

Keyterms Prompt:

Canistracci Oil
PJSIP
invoice desk

Custom Spelling:

canistracci:Canistracci
pj sip:PJSIP

Language:

US English

Speech To Text Engine API password:

fictional-assemblyai-token

Transcribe phone call recordings:

Every 10 minutes

Docs processing node

☒ Transcribe when recording is uploaded

Minimum call time for transcript:

30

Test speech recognition:

Choose File

No file chosen

Test

Admin Settings Speech to Text configuration for AssemblyAI with fictional documentation values.

Field	Meaning
Engine	Selects AssemblyAI as the global Speech to Text provider.
Endpoint server	AssemblyAI API host. Leave empty for the default host, or set a host such as <code>api.assemblyai.com</code> .
Model	AssemblyAI model used for transcript requests. Choose the model according to accuracy and fallback requirements.

Field	Meaning
Keyterms Prompt	One key term per line. Use it for tenant names, product names, department names, and PBX terms that should be recognized accurately.
Custom Spelling	One correction per line in the form <code>heard term:correct spelling</code> . Use it for brand names and technical words.
Language	AssemblyAI language selection. Automatic detection can be used when calls are multilingual or language is not predictable.
Speech To Text Engine API password	AssemblyAI API token.
Transcribe phone call recordings	Schedules transcript processing for recorded calls and selects the processing node.
Transcribe when recording is uploaded	Starts processing immediately after recording upload.
Minimum call time for transcript	Prevents short calls from being sent to AssemblyAI.
Test speech recognition	Uploads a WAV file to test the AssemblyAI endpoint, model, token, and language settings.

GeminiAI

Speech to Text

Engine:

GeminiAI

Model:

gemini-2.5-flash

Model command:

Transcribe the call in its original language, identify speakers, and keep PBX terms such as IVR and PJSIP.

Voicemail model command:

Transcribe the voicemail message exactly, preserve the caller wording, and do not add a summary.

Language:

Any language

Speech To Text Engine API password:

fictional-gemini-api-key

Transcribe phone call recordings:

Every 10 minutes

Docs processing node

☒ Transcribe when recording is uploaded

Minimum call time for transcript:

30

Test speech recognition:

Choose File

No file chosen

Test

Admin Settings Speech to Text configuration for GeminiAI with fictional documentation values.

Field	Meaning
Engine	Selects GeminiAI for speech recognition through a generative AI model.
Model	Gemini model used for transcription. Choose the model according to the desired balance of speed, cost, and accuracy.
Model command	Instruction sent to the model for the transcription task. Leave it empty to use the default instruction, or provide global guidance such as speaker separation and PBX terminology handling.
Voicemail model command	Instruction sent to GeminiAI when transcribing voicemail messages. Leave it empty to use the regular model command, then the default instruction.
Language	Recognition language option for the GeminiAI request.
Speech To Text Engine API password	Gemini API key.
Transcribe phone call recordings	Schedules transcript processing for recorded calls and selects the processing node.
Transcribe when recording is uploaded	Starts processing immediately after recording upload.
Minimum call time for transcript	Prevents short recordings from being submitted to GeminiAI.
Test speech recognition	Uploads a WAV file and verifies the GeminiAI model, command, key, and language settings.

Operational Notes

- Configure provider credentials and run a test upload before enabling automatic transcription jobs.
- Use the existing transcript processing node for scheduled jobs. Do not add a node only for documentation examples.
- External transcription services can process sensitive call audio. Review privacy, retention, billing, and data-processing requirements before enabling them globally.
- Tenant-level Speech to Text settings can override global engine, language, and credentials when a tenant requires different behavior.

Generative Artificial Intelligent chat models

Generative Artificial Intelligent chat models

Engine: No AI support

Summarize transcribed phone call recordings: Not scheduled

Please assign the default summariz

☐ Summarize when recording is transcribed

Sentimental analyze transcribed phone call recordings: Not scheduled

Please assign the default sentiment

☐ Sentimental analysis when recording is transcribed

Generative Artificial Intelligent chat models section of Admin Settings.

Use this section to configure AI chat-model access used by summary and analysis features.

Field or option	Purpose
Engine (Select)	Selects the Engine behavior for Generative Artificial Intelligent chat models.
API key	API Key to use
Model	Model: The model for the ChatGPT
Temperature	Temperature: Controls the randomness or creativity of the AI model output. Leave empty to use the provider default.
System content (Text area)	System content: Initialize the system content
Summarize user content (Text area)	Summarize user content: Provide the user content to summarize, use \${TRANSCRIPT} for the transcript
Voicemail summarize user content (Text area)	Voicemail summarize user content: Provide the user content to summarize voicemail messages, use \${TRANSCRIPT} for the transcript. If empty, the summarize user content is used.
Summarize transcribed phone call recordings (Select)	Summarize transcribed phone call recordings: Schedule the summarize for transcribed phone calls
Summarize when recording is transcribed (Checkbox)	Summarize when recording is transcribed: By enabling this, the summarize process will start immediately after the recording is transcribed
Sentimental analysis user content (Text area)	Sentimental analysis user content: Provide the user content to perform sentimental analysis, use \${TRANSCRIPT} for the transcript
Sentimental analyze transcribed phone call recordings (Select)	Sentimental analyze transcribed phone call recordings: Schedule the sentimental analysis for transcribed phone calls
Sentimental analysis when recording is transcribed (Checkbox)	Sentimental analysis when recording is transcribed: By enabling this, the sentimental analysis process will start immediately after the recording is transcribed

Field or option	Purpose
Recording processing email notifications (Select)	Controls whether every requested processing email is sent or only the highest requested result for each recipient.

Recording processing email notifications

This global setting controls which emails are sent when transcript, summary, and sentimental analysis processing is requested for the same call. Tenants using **System Default** inherit this value.

Option	Behavior
Always send the notification	Sends every requested transcript, summary, and sentimental analysis notification. This is used when no value has previously been configured.
Send the notification only for the last process	For each email recipient, sends only the highest requested processing result.

Last-process mode uses this priority: **sentimental analysis > summary > transcript**. A higher process suppresses a lower email only when email notification was requested for the same recipient. Email matching is case-insensitive, so recipients requested only for a lower process continue to receive that lower-process notification.

For example, if transcript notification is requested for A and B, summary for B and C, and sentimental analysis for C and D, A receives the transcript, B receives the summary, and C and D receive the sentimental analysis.

Suppression is based on the requested processing stage. If a higher process later fails, MiRTA PBX does not send a lower-stage fallback notification.

Fax Protocol

Fax Protocol

Modem Type:

Minimum Speed:

Maximum Speed:

Error Correction Mode (ECM):

Fax Protocol section of Admin Settings.

Use this section for modem protocol, speed, and ECM defaults used by fax processing.

Field or option	Purpose
Modem Type	Sets the Modem Type value for Fax Protocol.
Minimum Speed	Sets the Minimum Speed value for Fax Protocol.
Maximum Speed	Sets the Maximum Speed value for Fax Protocol.
Error Correction Mode (ECM) (Select)	Selects the Error Correction Mode (ECM) behavior for Fax Protocol.

Outbound Fax Service

Outbound Fax Service

Rescheduling delay (minutes):

1

Max number of attempts:

10

Force codec:

Fax Protocol:

T.38/G.711

▼

Show only Fax DIDs:

No

▼

Fast OnNet Fax processing:

No

▼

Default page format:

No page format selected

▼

Outbound Fax Service section of Admin Settings.

Use this section to control outbound fax retry behavior, protocol choices, DID filtering, and page format defaults.

Field or option	Purpose
Rescheduling delay (minutes)	Sets the Rescheduling delay (minutes) value for Outbound Fax Service.
Max number of attempts	Sets the Max number of attempts value for Outbound Fax Service.
Force codec	Force codec: When dialing out a fax, request only the entered codec
Fax Protocol (Select)	Selects the Fax Protocol behavior for Outbound Fax Service.

Field or option	Purpose
Show only Fax DIDs (Select)	Selects the Show only Fax DIDs behavior for Outbound Fax Service.
Fast OnNet Fax processing (Select)	Fast OnNet Fax processing: When a fax is directed to an onnet number, just copy the fax to the destination, without really sending it
Default page format (Select)	Default page format: When a fax is sent and no page format is selected, this one is used

Inbound Fax Service

Inbound Fax Service

Sender Email name: *****

Sender Email address: *****

Automatic fax detection time: 3

Fax file name format: fax-\$(UNIQUEID).pdf

Inbound Fax Service section of Admin Settings.

Use this section for inbound fax sender identity, detection timing, and generated fax file names.

Field or option	Purpose
Sender Email name	Sender Email name: If no template is defined for the inbound fax service email, this sender email name will be used
Sender Email address	Sender Email address: If no template is defined for the inbound fax service email, this sender email address will be used
Automatic fax detection time	Number of seconds to wait for remote fax tone when DID set to autodetect faxes. It adds a delay in reception of calls when DID set to autodetect faxes.
Fax file name format (Select)	When delivering the fax by email, a different file name format can be used

Mail to Fax Service

Mail to Fax Service

Network activity timeout:

60

Automatic disable after X failures:

0

Mail to Fax Service section of Admin Settings.

Use this section for network timeout and automatic disable behavior for mail-to-fax processing.

Field or option	Purpose
Network activity timeout	Network activity timeout: Mailboxes are checked serially, this will set the amount of time to wait for any network I/O operation, in seconds
Automatic disable after X failures	Automatic disable after X failures: After configured failures, automatic disable the mailbox, use 0 to disable the feature

Mail to Call Service

Mail to Call Service

Network activity timeout:

60

Automatic disable after X failures:

0

Mail to Call Service section of Admin Settings.

Use this section for network timeout and automatic disable behavior for mail-to-call processing.

Field or option	Purpose
Network activity timeout	Network activity timeout: Mailboxes are checked serially, this will set the amount of time to wait for any network I/O operation, in seconds
Automatic disable after X failures	Automatic disable after X failures: After configured failures, automatic disable the mailbox, use 0 to disable the feature

User Authentication - LDAP

User Authentication - LDAP

Base DN: *****

Account Suffix: *****

Account Prefix: *****

Domain Controllers: *****

Test Username: *****

Test Password: *****

Test LDAP

User Authentication - LDAP section of Admin Settings.

Use this section to configure LDAP binding and test credentials for external authentication.

Field or option	Purpose
Base DN	Base DN: The base DN, like ou=users,dc=company,dc=local
Account Suffix	Account Suffix: Like ou=sysops
Account Prefix	Account Prefix: Like cn=
Domain Controllers	Domain Controllres: List the domain controllers including the protocol, like ldap://dc1.company.com,ldap://dc2.company.com
Test Username	Test Username: The username will be joined in a string like {Account Prefix}{Username},{Account Suffix},{Base DN}
Test Password	Sets the Test Password value for User Authentication - LDAP.

Conferencing

Conferencing

Sender Email name: *****

Sender Email address: *****

Conferencing section of Admin Settings.

Use this section for conference email sender defaults.

Field or option	Purpose
-----------------	---------

Sender Email name	Sets the Sender Email name value for Conferencing.
Sender Email address	Sets the Sender Email address value for Conferencing.

Voicemail

Voicemail

Audio format configured: WAV

Voicemail section of Admin Settings.

Use this section for voicemail audio format visibility and defaults.

Field or option	Purpose
Audio format configured (Select)	Audio format configured: Set to the audio format chosen in /etc/asterisk/voicemail.conf. This is not for choosing the voicemail audio format, but to make the web interface use the same audio format chosen in the voicemail configuration file.

Voicemail backup

Voicemail backup

Storage type: No Storage

Voicemail recording name: Voicemail, Date, time, SRC and DST

Voicemail backup section of Admin Settings.

Use this section to configure backup storage for voicemail messages.

Field or option	Purpose
Storage type (Select)	Storage type: Sets the storage backend for voicemail backup. There is no data retention limit.
Host (Select)	Host: If your FTP server is not using the standard port 21, you can configure the desired port using a host:port syntax.
User	Sets the User value for Voicemail backup.
Password	Sets the Password value for Voicemail backup.

Field or option	Purpose
Directory	Sets the Directory value for Voicemail backup.
Voicemail recording name (Select)	Voicemail recording name: You can choose the name of the recording.

Provisioning

Provisioning

Provisioning host name: *****

Blacklisted autoprovisioning files:

Fast provisioning QR Code:

Provisioning section of Admin Settings.

Use this section for provisioning host, blocked provisioning files, and fast-provisioning QR code format.

Field or option	Purpose
Provisioning host name	Provisioning host name: Set the provisioning host name reported in the Configuration/Provisioning/Phones page. If left blank will automatically use the one defined in the theme selected, in the tenant or the host name used to access the web interface.
Blacklisted autoprovisioning files (Text area)	Blacklisted autoprovisioning files: If a file matches one of these regex, then the usual MAC matching is disabled and only a custom file can be served, if available
Fast provisioning QR Code	Fast provisioning QR Code: If enabled in the tenant, create a QR Code in the Configuration/Extensions page to provision the extension on supporting softphones. You can use the following variables: \$username, \$secret, \$macaddress, \$password, \$http_user and \$http_password

Inbound Unassigned DIDs

Inbound Unassigned DIDs

Alert Email address: *****

Media file to play:

Choose FileNo file chosen

Inbound Unassigned DIDs section of Admin Settings.

Use this section for alerting and media playback when an inbound DID is not assigned.

Field or option	Purpose
Alert Email address	Sets the Alert Email address value for Inbound Unassigned DIDs.
Media file to play	Sets the Media file to play value for Inbound Unassigned DIDs.

Disabled Tenants

Disabled Tenants

Inbound calls file to play:

Choose FileNo file chosen

Outbound calls file to play:

Choose FileNo file chosen

Disabled Tenants section of Admin Settings.

Use this section for the media played when disabled tenants receive or place calls.

Field or option	Purpose
Inbound calls file to play	Sets the Inbound calls file to play value for Disabled Tenants.
Outbound calls file to play	Sets the Outbound calls file to play value for Disabled Tenants.

CSV Exports

CSV Exports

Delimiter:

Enclosure:

Escape char:

BOM sequence:

No BOM sequence

CSV Exports section of Admin Settings.

Use this section for CSV delimiter, enclosure, escape, and BOM defaults.

Field or option	Purpose
Delimiter	Sets the Delimiter value for CSV Exports.
Enclosure	Sets the Enclosure value for CSV Exports.
Escape char	Sets the Escape char value for CSV Exports.
BOM sequence (Select)	Selects the BOM sequence behavior for CSV Exports.

Inbound calls

Inbound calls

Privacy:

Follow RFC guidelines

Inbound calls section of Admin Settings.

Use this section for inbound privacy defaults.

Field or option	Purpose
Privacy (Select)	Selects the Privacy behavior for Inbound calls.

Outbound calls

Outbound calls

On Busy - media file to play:

Choose File No file chosen

On Do Not Call list - media file to play:

Choose File No file chosen

Minimum call time in seconds:

Failed call reported as:

Congestion ▼

Outbound calls section of Admin Settings.

Use this section for busy or blocked-call media, minimum call time, and failed-call reporting.

Field or option	Purpose
On Busy - media file to play	Sets the On Busy - media file to play value for Outbound calls.
On Do Not Call list - media file to play	Sets the On Do Not Call list - media file to play value for Outbound calls.
Minimum call time in seconds	Minimum call time in second: Enter the minimum call time, in seconds, otherwise the call will be not even started
Failed call reported as (Select)	Failed call reported as: When a call is unroutable or all providers fail to connect, report as

CNAM service

CNAM service

URL/custom AGI script:

☐ Request only when CallerID name is empty

☐ Allow UTF-8 characters and symbols

☐ Caching

Cache retention (days):

Manage CNAM Cache

CNAM service section of Admin Settings.

Use this section to configure caller-name lookup, caching, and UTF-8 handling.

Field or option	Purpose
URL/custom AGI script	URL: Enter the CNAM URL using %%NUM%% as placeholder for the number of phone. Or the name of an agi script returning the CNAM value As example for OpenCNAM: https://api.opencnam.com/v2/phone/%%NUM%%?format=pbx&account_sid=ACCOUNT_SID&auth_token=AUTH_TOKEN replacing ACCOUNT_SID and AUTH_TOKEN with the one provided by OpenCNAM
Request only when CallerID name is empty (Checkbox)	Enables or disables Request only when CallerID name is empty.
Allow UTF-8 characters and symbols (Checkbox)	Enables or disables Allow UTF-8 characters and symbols.
Caching (Checkbox)	Enables or disables Caching.
Cache retention (days)	Sets the Cache retention (days) value for CNAM service.
Manage CNAM Cache (Action)	Opens or runs the related administration action.

Switchboard

Switchboard

Websocket hostname:port to connect:

SSL Usage:

Yes

Switchboard section of Admin Settings.

Use this section for switchboard websocket connection defaults.

Field or option	Purpose
Websocket hostname:port to connect	Websocket hostname:port to connect: This is the fully qualified domain name of server running the AMI Router
SSL Usage (Select)	SSL usage: Here you define if the client javascript application will talk to the host using SSL or not.

WebRTC

WebRTC

Chan_sip WebRTC SIP server:

PJSIP WebRTC SIP server:

pbx.mirtapbx.com

Chan_sip realm for registration:

PJSIP realm for registration:

pbx.mirtapbx.com

Websocket proxy URL for chan_sip:

Websocket proxy URL for PJSIP:

Softphone user agent:

WebRTC section of Admin Settings.

Use this section for WebRTC SIP servers, realms, websocket proxies, and softphone user-agent settings.

Field or option	Purpose
Chan_sip WebRTC SIP server	Chan_sip WebRTC server: When authenticating with a chan_sip account, this server will be used for the WebRTC SIP phone.
PJSIP WebRTC SIP server	PJSIP WebRTC server: When authenticating with a PJSIP account, this server will be used for the WebRTC SIP phone.
Chan_sip realm for registration	Chan_sip realm for registration: Server realm to be used by the switchboard extensions to register using chan_sip.
PJSIP realm for registration	PJSIP realm for registration: Server realm to be used by the switchboard extensions to register using PJSIP.
Websocket proxy URL for chan_sip	Websocket proxy URL for chan_sip: This is the websocket proxy URL to use for switchboard extensions to register when using chan_sip.
Websocket proxy URL for PJSIP	Websocket proxy URL for PJSIP: This is the websocket proxy URL to use for switchboard extensions to register when using PJSIP.
Softphone user agent	Softphone user agent: The user agent to report to the system.

SMS

SMS

Show CallerID DIDs for SMS:

Show any DIDs

▼

Max SMS length:

SMS section of Admin Settings.

Use this section for SMS DID filtering and SMS length limits.

Field or option	Purpose
Show CallerID DIDs for SMS (Select)	Show CallerID DIDs for SMS: Permit to Show only DIDs configured to receive SMS
Max SMS length	Max SMS length: Enter the max number of character accepted for an SMS in the portal

Security

Security

☐ Hide Password in main screens

☐ Allow to show hidden Password in main screens

☐ Use split cost limits (domestic/international)

WebRTC SSL path:

Change password enforcement regex:

Change password enforcement message:

Special characters in auto generated passwords:

System password expiration days:

Use Google reCAPTCHA:

Never

reCAPTCHA site key:

reCAPTCHA secret key:

2FA tenant for SMS sending:

No SMS allowed

2FA SMS message:

2FA SMS callerid:

☐ Allow extensions with custom usernames

☐ Requires unique Web usernames

☐ Increased Session Cookies security

Security section of Admin Settings.

Use this section for password visibility, password policy, reCAPTCHA, two-factor authentication, custom extension usernames, web username uniqueness, and session-cookie hardening.

Field or option	Purpose
Hide Password in main screens (Checkbox)	Enables or disables Hide Password in main screens.
Allow to show hidden Password in main screens (Checkbox)	Enables or disables Allow to show hidden Password in main screens.
Use split cost limits (domestic/international) (Checkbox)	Enables or disables Use split cost limits (domestic/international).
WebRTC SSL path	WebRTC SSL path: Enter the full path, usually /etc/asterisk/certificates/yourdomain.pem to allow WebRTC clients. You need to reload the sip module or prune the clients when this is updated

Field or option	Purpose
Change password enforcement regex	Change password enforcement regex: Enter the regex to use for passwords entered by the user in the Login/Change Password
Change password enforcement message	Change password enforcement message: Enter the message to use when the passwords entered by the user in the Login/Change Password doesn't meet the required regex
Special characters in auto generated passwords	Special characters in auto generated passwords: List of special characters used in the auto generation of passwords. Some softphones or provisioning templates can't use any character
System password expiration days	System password expiration days: Request a password change for system users after defined days since last change. Leave blank to disable password expiration.
Disable inactive users after days	Automatically disables system users and extension web users when their last successful login is older than the configured number of days. Use 0 to disable future automatic inactivity checks.
Use Google reCAPTCHA (Select)	SSL usage: Use Google reCAPTCHA
reCAPTCHA site key	reCAPTCHA site key: You need to register on google.com and obtain a reCAPTCHA API key for your list of domains
reCAPTCHA secret key	reCAPTCHA secret key: You need to register on google.com and obtain a reCAPTCHA API key for your list of domains
2FA tenant for SMS sending (Select)	Selects the 2FA tenant for SMS sending behavior for Security.
2FA SMS message	2FA SMS message: This is the message delivering the code for 2FA authentication, use %%CODE%% for replace the actual code
2FA SMS callerid	2FA SMS callerid: This is the callerid to use when delivering the code for 2FA authentication
Allow extensions with custom usernames (Checkbox)	Allow extensions with custom usernames: Allow to create extensions with custom usernames.
Requires unique Web usernames (Checkbox)	Require unique Web usernames: Requires extension web usernames to be unique among all the tenants.
Increased Session Cookies security (Checkbox)	Increased Session Cookies security: Activate several restriction on the session cookie usage to increase security.

Inactive-user disablement

Daily housekeeping applies this policy only when **Disable inactive users after days** is greater than 0. Accounts with no successful login history are ignored, and the built-in **admin** system user is exempt.

A successful portal login updates the system-user or extension-user timestamp after password, IP filter, two-factor authentication, and password-expiration checks complete. An authorized switchboard login also updates the extension-user timestamp. SIP registration and WebRTC credential requests are not affected and do not update the timestamp.

Changing the setting to 0 stops future automatic disablement but does not restore accounts already disabled. Open the system user or extension, select **Re-enable on save**, and save. The historical last-login timestamp is retained and the account receives one configured inactivity period of grace.

Logging

Logging

☒ Log Extension Events

☒ Log Provision Activities

☐ Device state pedantic commit

☒ Device state logging

☐ Monitor DID for BLF

☐ PHP Error reporting

Logging section of Admin Settings.

Use this section for extension event logging, provisioning activity logging, device-state logging, latency logging, and PHP error reporting.

Field or option	Purpose
Log Extension Events (Checkbox)	Log Extension Events: Log any change in the extension state, you can review these logs from Status/Peers
Log Provision Activities (Checkbox)	Log Provision Activities: Log any provision request from phones
Device state pedantic commit (Checkbox)	Device state pedantic commit: Rewrite the state of extension at every registration, even if the state has not changed
Device state logging (Checkbox)	Device state logging: Log any devstate activity using syslog
Monitor DID for BLF (Checkbox)	Monitor DID for BLF: Monitor any DID state for BLF

Field or option	Purpose
PHP Error reporting (Checkbox)	PHP Error reporting: Show all the bad PHP coding, warnings and errors. You don't need it.

Music On Hold

Music On Hold

Default Music On Hold:

Asterisk Standard

▼

Default Music On Hold streaming engine:

mpg123

▼

Music On Hold mode:

Custom (suitable for any Asterisk version)

▼

Music On Hold section of Admin Settings.

Use this section for default music-on-hold selection and streaming mode.

Field or option	Purpose
Default Music On Hold (Select)	Selects the Default Music On Hold behavior for Music On Hold.
Default Music On Hold streaming engine (Select)	Selects the Default Music On Hold streaming engine behavior for Music On Hold.
Music On Hold mode (Select)	Selects the Music On Hold mode behavior for Music On Hold.

Stats

Stats

Count transfer as answered:

No

▼

Stats section of Admin Settings.

Use this section for statistics calculation behavior.

Field or option	Purpose
Count transfer as answered (Select)	Agent Activity: Count transferred calls, even parked, as answered calls.

MS Teams integration

MS Teams integration

MS Teams integration:

Disabled

▼

OpenSIPS socket:

OpenSIPS server connection:

Please assign the server with the OpenSIPS connection

▼

MS Teams integration section of Admin Settings.

Use this section for Microsoft Teams integration and OpenSIPS connectivity.

Field or option	Purpose
MS Teams integration (Select)	MS Teams integration: Enable the MS Teams integration. You need to define the MS Teams address in the Admin/Tenant
OpenSIPS socket	OpenSIPS socket: Something like <code>tls:__ip_address__:5067</code> where the OpenSIPS is listening
OpenSIPS server connection (Select)	OpenSIPS server connection: The server who has the connection to the OpenSIPS server

QueueMetrics API

QueueMetrics API

QueueMetrics API:

Disabled

▼

QueueMetrics delay:

QueueMetrics API section of Admin Settings.

Use this section for QueueMetrics integration behavior.

Field or option	Purpose
QueueMetrics API (Select)	QueueMetrics API: Enable the QueueMetrics API by sending to QueueMetrics the logs from the selected queues
QueueMetrics delay	QueueMetrics delay: How many milliseconds to wait between two API calls to QueueMetrics

Theming

Theming

☒ Let's Encrypt certificates creation from Admin/Themes page

Virtual Host directory:

Virtualhost Template:

Theming section of Admin Settings.

Use this section for theme-related certificate and virtual-host defaults.

Field or option	Purpose
Let's Encrypt certificates creation from Admin/Themes page (Checkbox)	Let's Encrypt certificates creation from Admin/Themes page: Allow the system to automatically generate and optionally renew Let's Encrypt certificates
Virtual Host directory	Virtual Host directory: Allow the system to automatically generate virtual host configurations. Usually it is /etc/httpd/conf.d
Virtualhost Template (Text area)	Sets the Virtualhost Template value for Theming.

Queue History Theming

Queue History Theming

Queue History easy filters:

Do not show easy filters

Queue History Theming section of Admin Settings.

Use this section for queue-history filtering behavior.

Field or option	Purpose
Queue History easy filters (Select)	Queue History easy filters: In Status/Queue History show easy filters like in Status/Stats.

Dashboard Theming

Dashboard Theming

Call quantity most recent day: Yesterday

Dashboard Theming section of Admin Settings.

Use this section for dashboard chart defaults.

Field or option	Purpose
Call quantity most recent day (Select)	Call quantity most recent day: Most recent day to show in the Call Quantity tab.

Call History Theming

Call History Theming

Call History view: Show all legs

Call History easy filters: Do not show easy filters

Call History mobile view: Do not show mobile view

Call History destination view: Show dialed and expanded digits

Call History row count: Always count the number of rows

Call History number of rows preloaded: 500

Call History wherelanded preprocessing: Not scheduled

Demo server

Call History Theming section of Admin Settings.

Use this section for call-history display, filtering, row loading, and preprocessing behavior.

Field or option	Purpose
Call History view (Select)	Call History view: In Status/Call History controls if to show all legs or try to show compact by grouping them.
Call History easy filters (Select)	Call History easy filters: In Status/Call History show easy filters like in Status/Stats.
Call History mobile view (Select)	Call History mobile view: In Status/Call History show a mobile phone optimized view when using a smartphone
Call History destination view (Select)	Call History destination view: In Status/Call History controls how to display the destination number dialed.

Field or option	Purpose
Call History row count (Select)	Call History row count: Counting every row in the Call History is slow and most of the time, useless. Using this option you can speed up the counting of rows
Call History number of rows preloaded	Call History number of rows preloaded: Specifies how many rows to preload when loading the Call History
Call History wherelanded preprocessing (Select)	Call history wherelanded preprocessing: Accessing the call history can be slow because the system needs to compute each call real destination. You can schedule a preprocessing to speed up access to Call history

Advanced Customization

Advanced Customization

☒ Show status of extension in Configuration/Extensions page

☒ Show status of extension in Status/Peers page

DID Format: **Three fields: (International prefix) area code - number** ▼

☒ National form in DID select

☒ National form with no trunk in DID select

☒ E.164 form in DID select

☐ E.164 with plus in DID select

☐ E.164 with international prefix in DID select

☒ Show + in DID numbers

☐ Ignores digits after # or ;

☐ Admins see all tenants

☒ Use advanced filters

☒ Use filter toolbar

☐ Use DIDs storage

☒ Use translations

☐ Use branches and departments

☒ Alert on NAT IP/port duplicate

☐ Permit HTTP usage

☒ Kill MOH process after 60 minutes

SIP Trunk Module: **Chan_sip** ▼

Diversion Host: **diversion.example.com**

Session duration:

☐ Lock facilities (queue, parking lots and conference rooms) to the assigned server

Queue Stats Reset: **Reset manually** ▼

jqGrid tenant selection: **Tenant Code** ▼

SIP stack available: **chan_sip and PJSIP** ▼

Preferred SIP stack: **chan_sip** ▼

First day in date and time picker: **Sunday** ▼

LCR Prefix for expansion: **4**

MAX TTL for calls:

MAX TTL alert Email: *********

Tenant Selector Format: **Only Tenant Name** ▼

Admin Settings Advanced Customization section with the Diversion Host setting shown with fictional documentation data.


Use this section for advanced UI, DID format, tenant visibility, SIP Diversion header host handling, SIP stack, cron server, language, and low-level routing defaults.

Field or option	Purpose
Show status of extension in Configuration/Extensions page (Checkbox)	Enables or disables Show status of extension in Configuration/Extensions page.
Show status of extension in Status/Peers page (Checkbox)	Enables or disables Show status of extension in Status/Peers page.
DID Format (Select)	Selects the DID Format behavior for Advanced Customization.
National form in DID select (Checkbox)	Enables or disables National form in DID select.
National form with no trunk in DID select (Checkbox)	Enables or disables National form with no trunk in DID select.
E.164 form in DID select (Checkbox)	Enables or disables E.164 form in DID select.
E.164 with plus in DID select (Checkbox)	Enables or disables E.164 with plus in DID select.
E.164 with international prefix in DID select (Checkbox)	Enables or disables E.164 with international prefix in DID select.
Show + in DID numbers (Checkbox)	Enables or disables Show + in DID numbers.
Ignores digits after # or ; (Checkbox)	Enables or disables Ignores digits after # or ;.
Admins see all tenants (Checkbox)	Enables or disables Admins see all tenants.
Use advanced filters (Checkbox)	Enables or disables Use advanced filters.
Use filter toolbar (Checkbox)	Enables or disables Use filter toolbar.
Use DIDs storage (Checkbox)	Enables or disables Use DIDs storage.
Use translations (Checkbox)	Enables or disables Use translations.
Use branches and departments (Checkbox)	Enables or disables Use branches and departments.
Alert on NAT IP/port duplicate (Checkbox)	Enables or disables Alert on NAT IP/port duplicate.
Permit HTTP usage (Checkbox)	Enables or disables Permit HTTP usage.
Kill MOH process after 60 minutes (Checkbox)	Enables or disables Kill MOH process after 60 minutes.
SIP Trunk Module (Select)	SIP Trunk Module: Use the defined asterisk module when passing the call from one server to the other
Diversion Host	Diversion Host: Host to use in SIP Diversion headers. Leave empty to use the system name.
Session duration	Session duration is read from php.ini, but it can be set here (in seconds). 1 hour are 3600 seconds.

Field or option	Purpose
Lock facilities (queue, parking lots and conference rooms) to the assigned server (Checkbox)	Lock facilities: When defining a queue, a conference room or a parking lot, you need to assign them to one of your servers. If left to be assigned automatically, they will be run from the first server trying to use it. They will be moved to another server when the server where they are assigned will stop answering. You can lock them to one server, so they will not be reassigned to another server if the server running them will be temporarily not answering.
Queue Stats Reset (Select)	Queue Stats Reset: Reset the Asterisk maintained stats like SLA and SLA2 at midnight.
jqGrid tenant selection (Select)	Selects the jqGrid tenant selection behavior for Advanced Customization.
SIP stack available (Select)	Selects the SIP stack available behavior for Advanced Customization.
Preferred SIP stack (Select)	Selects the Preferred SIP stack behavior for Advanced Customization.
First day in date and time picker (Select)	Selects the First day in date and time picker behavior for Advanced Customization.
LCR Prefix for expansion	Sets the LCR Prefix for expansion value for Advanced Customization.
MAX TTL for calls	MAX TTL for calls: A call can trigger several destinations, each destination can trigger several other destinations. To avoid loops or infinite running calls, a maximal number of steps can be set for any call. By default it is 100.
MAX TTL alert Email	MAX TTL alert Email: When a TTL expires it can be due to a loop. A loop is dangerous because it uses lots of CPU power. You can be noticed when it happens.
Tenant Selector Format (Select)	Selects the Tenant Selector Format behavior for Advanced Customization.
Default cronjob server (Select)	Selects the Default cronjob server behavior for Advanced Customization.
Default campaign server (Select)	Selects the Default campaign server behavior for Advanced Customization.
Default SMS server (Select)	Selects the Default SMS server behavior for Advanced Customization.
Campaign "fast start" delay	Campaign fast start delay: Campaigns to be started are checked every minute. This means, when starting a campaign using a feature code, it can take up to 60 seconds before it really starts. You can configure here a delay in seconds, activating a more fine check for campaign start. Setting to empty, will stop the fast start feature.

Field or option	Purpose
Default fax server (Select)	Selects the Default fax server behavior for Advanced Customization.
Available Languages	Sets the Available Languages value for Advanced Customization.
Custom peer status page query	Custom peer status page query: You can provide a query to be executed for each of the peers in peer status, returning a list of fields. Use %%PEERNAME%% for the peer name, like select mailbox as Mailbox,allow as Allow from sipfriends where data-inputname=
Save, Save (Action)	Opens or runs the related administration action.

Administration Links



Administration Links section of Admin Settings.

Use this side panel to open related global administration tools.

Field or option	Purpose
Languages (Action)	Opens the related global administration page.
Codecs (Action)	Opens the related global administration page.
Date and time formats (Action)	Opens the related global administration page.
Ring tones (Action)	Opens the related global administration page.
Regions (Action)	Opens the related global administration page.
Backups (Action)	Opens the related global administration page.
Auto Answers (Action)	Opens the related global administration page.

Field or option	Purpose
Digital Faxes (Action)	Opens the related global administration page.
Default Quick shortcuts (Action)	Opens the related global administration page.
Push Notifications (Action)	Opens the related global administration page.
System Messages (Action)	Opens the related global administration page.
SIP Cause Codes (Action)	Opens the related global administration page.

Upgrade and Version

Use this area to check the installed software version, available versions, database schema version, and controlled upgrade or reinstall actions.

Dialing and Internationalization

Configure currency, international prefix, trunk prefix, country code, language, DID matching, caller ID enforcement, and outbound digit restrictions.

Security and Access

Configure global access, API behavior, password rules, tenant visibility, SIP scanner protection, and security-related defaults.


Backups

Use **Admin > Settings > Backups** to create and maintain system backup schedules. These are global schedules, not tenant schedules. A backup can export system configuration, call history, recording metadata, reports data, custom configuration files, or a combination of these sources.

This page documents the dedicated Backups administration screen. It is separate from the **Voicemail backup** storage setting inside Admin Settings, which only controls voicemail-message backup storage.

Open the Backups Page

Step	Action
1	Open Admin > Settings from the Global Administration menu.
2	In the Administration Links panel, choose Backups.
3	Use the Backups list to review existing schedules, run a backup manually, or open the Backup form.



Admin Settings Backups list from the current MiRTA PBX application, with operational values sanitized.

Backups List

The Backups list is the operational view for existing backup schedules. It supports sorting, search, pagination, selecting rows for deletion, opening a schedule by clicking its linked fields, and queuing a manual run from the Action column.

Column or control	Description
New Backup	Opens a blank Backup form for creating a new global backup schedule.
Delete Selected	Deletes the selected backup schedules after confirmation. Each deleted schedule also removes the linked background cron definition.
Selection checkbox	Selects one or more backup schedules for bulk deletion.
Name	Schedule name. A red disabled icon beside the name indicates an inactive schedule.
Node	Node that runs the backup job. Use this to keep database dumps and file operations on the intended PBX node.
Scheduled	Human-readable schedule built from month, weekday, day, hour, and minute settings.
Last executed	Shows the last start and end timestamps for the background job.
Directory	Local filesystem directory where backup files are written before optional FTP transfer.
FTP Server	Remote FTP host and directory when FTP storage is configured.
Run backup	Queues the selected schedule for immediate execution. The application displays that the backup has been scheduled and should start within about one minute.

Backup Information

The Information section defines the schedule identity, whether it is active, what data the backup contains, and which node runs the job.

Information

Name:

Active:

Type:

Run from node:

Backup Information section from the current MiRTA PBX application, using unsaved documentation values.

Field	Description
Name	Required schedule name shown in the Backups list and background job history.
Active	Controls whether the scheduled job can run automatically. Inactive schedules remain saved but are not executed by schedule.
Type	Selects the backup content. Available choices include system configuration, call history, recordings metadata, reports data, combined system and call history backups, combined system, call history, and recordings backups, combined system, call history, recordings, and reports data backups, and custom configuration files.
Run from node	Selects the PBX node that executes the backup. Choose a node that has access to the database, local backup directory, and any custom files being archived.

Backup Content Types

Backup content	What is created
System configuration	Creates a system configuration database dump named like <code>asterisk-YYYY-MM-DD_HH-MM-SS.sql</code> . The recording metadata and reports data tables are excluded from this dump and handled by their own backup choices.
Call history	Creates a call-history database dump named like <code>asteriskcdrdb-YYYY-MM-DD_HH-MM-SS.sql</code> .
Recordings	Creates a recording metadata database dump named like <code>asteriskrecordings-YYYY-MM-DD_HH-MM-SS.sql</code> . This backs up the recordings database table; it does not replace the configured storage backup for the actual audio files.
Reports data	Creates a reports data database dump named like <code>asteriskreportsdata-YYYY-MM-DD_HH-MM-SS.sql</code> .
System configuration then call history	Runs the system configuration dump and then the call-history dump in the same backup job.
System configuration then call history then recordings	Runs the system configuration, call-history, and recording-metadata dumps in the same backup job.
System configuration then call history then recordings and reports data	Runs the combined database backup including system configuration, call history, recording metadata, and reports data.
Custom configuration files	Creates a compressed archive named like <code>customfiles-YYYY-MM-DD_HH-MM-SS.tar.gz</code> containing the custom system and PBX configuration paths handled by the backup runner.

Schedule

The Schedule section controls when the background job runs. Month, weekday, day, and hour support multiple selections; minute is selected as a single value.

Schedule

Month:

Please select months for execution

Weekday:

Please select weekdays for execution

Day:

Please select days for execution

Hour:

Please select hours for execution

Minute:

15

Backup Schedule section from the current MiRTA PBX application, using unsaved documentation values.

Field	Description
Month	Select Every month or one or more specific months.
Weekday	Select Any weekday or one or more weekdays. This is evaluated together with the other schedule fields.
Day	Select Every day or one or more day numbers from 1 through 31.
Hour	Select Every hour or one or more hours from 0 through 23.
Minute	Select Every minute or one minute from 00 through 59. For production backups, prefer a specific low-traffic minute instead of every minute.

Database Access

The backup job uses these credentials when creating database dumps. Store credentials for an account that can read the required MiRTA PBX databases and run from the selected node.

Database access

Host:

127.0.0.1

User:

backup_user

Password:

Backup Database access section from the current MiRTA PBX application, with credentials sanitized.

Field	Description
Host	Database host reachable from the selected node. Use the local database address when the backup runs on the database node.
User	Database user used by the dump command.
Password	Database password for the backup user. Treat it as a secret and avoid exposing it in screenshots or support tickets.

Filesystem Backup Storage

Filesystem storage is always the first backup target. The backup runner creates files in the configured local directory and applies local retention by backup type.

Filesystem backup storage

Directory:

/var/backups/mirtapbx

System configuration #files:

14

Call history #files:

14

Recordings #files:

14

Reports data #files:

14

Custom configuration #files:

7

Backup Filesystem backup storage section from the current MiRTA PBX application, using documentation paths and retention values.

Field	Description
-------	-------------

Directory	Required local directory where backup files are written. The selected node must be able to create the directory if needed and write files into it.
System configuration #files	Required number of local system configuration dump files to keep.
Call history #files	Required number of local call-history dump files to keep.
Recordings #files	Required number of local recording metadata dump files to keep.
Reports data #files	Required number of local reports data dump files to keep.
Custom configuration #files	Required number of local custom configuration archives to keep.

FTP Backup Storage

FTP storage is optional. When an FTP host is configured, the backup runner uploads the generated local backup files to the remote FTP directory and applies the configured remote retention values.

FTP backup storage

Host: backup.example.test

User: pbx-backup

Password: *****

Max data rate: 10M

Directory: /pbx/mirtapbx

☒ Use passive FTP

System configuration #files: 30

Call history #files: 30

Recordings #files: 30

Reports data #files: 30

Custom configuration #files: 12

Save

Delete

Back

Backup FTP backup storage section from the current MiRTA PBX application, using documentation server values.

Field	Description
Host	FTP server hostname or address. Leave empty to keep backups only in the local filesystem directory.
User	FTP username.
Password	FTP password. Treat it as a secret.
Max data rate	Optional upload limit. Use suffixes such as K, M, or G, for example 10M.
Directory	Remote FTP directory where backup files are uploaded.
Use passive FTP	Keeps passive FTP enabled when checked. Clear it only for FTP servers that require non-passive mode.
System configuration #files	Optional number of remote system configuration dump files to keep.
Call history #files	Optional number of remote call-history dump files to keep.
Recordings #files	Optional number of remote recording metadata dump files to keep.
Reports data #files	Optional number of remote reports data dump files to keep.
Custom configuration #files	Optional number of remote custom configuration archives to keep.
Save	Creates or updates the backup schedule and returns to the Backups list.
Delete	Deletes the current backup schedule after confirmation.
Back	Returns to the Backups list without saving changes.

More Panel

The More panel provides a second entry point for creating a new backup schedule and, when schedules already exist, quick links to open the other saved backup schedules.

More

New Backup schedule

Backup More panel from the current MiRTA PBX application, with schedule names sanitized.

Validation and Troubleshooting

Check	What to verify
Manual run	After saving a schedule, use the Run backup action from the Backups list and wait at least one minute for the background runner to pick it up.
Local files	Confirm that new backup files are created in the configured local directory and that old files are pruned according to the retention counts.
Database permissions	If database dumps fail, verify host reachability, username, password, and read permissions on the selected backup content databases.
Filesystem permissions	If no files are created, verify that the selected node can create and write to the configured directory.
FTP transfer	If local files are created but remote transfer fails, verify FTP host, directory, credentials, passive mode, transfer rate, and that the selected node has the FTP client dependency installed.
Background output	For low-level failure details, check the backup runner output log at <code>/tmp/mirtapbxbackup.out</code> and, when a post-backup hook is installed, <code>/tmp/mirtapbx-post-backup.log</code> .