

AAstra/Mitel 6869i - MAC request

[Back to Phone Model Examples](#)

```
{line_loop}
sip line{$line_m1} screen name: {$displayname}
sip line{$line_m1} user name: {$username}
sip line{$line_m1} display name: {$displayname}
sip line{$line_m1} vmail: *78
sip line{$line_m1} auth name: {$username}
sip line{$line_m1} password: {$secret}
sip line{$line_m1} mode: 0
sip line{$line_m1} proxy ip: {$server_host|demo.mirtapbx.com}
sip line{$line_m1} proxy port: {$server_port|5060}
sip line{$line_m1} registrar ip: {$server_host|demo.mirtapbx.com}
sip line{$line_m1} registrar port: {$server_port|5060}
sip line{$line_m1} registration period: 120
{/line_loop}

topsoftkey1 type: {$vpk1type||select|,blf,speeddial}
topsoftkey1 label: {$vpk1description||select|pickupname}
topsoftkey1 value: {$vpk1value||select|pickupextension}
topsoftkey1 line: {$vpk1account|1|select|Account 1=1,Account 2=2,Account 3=3}

topsoftkey2 type: {$vpk2type||select|,blf,speeddial}
topsoftkey2 label: {$vpk2description||select|pickupname}
topsoftkey2 value: {$vpk2value||select|pickupextension}
topsoftkey2 line: {$vpk2account|1|select|Account 1=1,Account 2=2,Account 3=3}

topsoftkey3 type: {$vpk3type||select|,blf,speeddial}
topsoftkey3 label: {$vpk3description||select|pickupname}
topsoftkey3 value: {$vpk3value||select|pickupextension}
topsoftkey3 line: {$vpk3account|1|select|Account 1=1,Account 2=2,Account 3=3}
```

```
topsoftkey4 type: {$vpk4type||select|,blf,speeddial}  
topsoftkey4 label: {$vpk4description||select|pickupname}  
topsoftkey4 value: {$vpk4value||select|pickupeextension}  
topsoftkey4 line: {$vpk4account|1|select|Account 1=1,Account 2=2,Account 3=3}
```

Revision #1

Created 2026-09-22 09:31:49 UTC by Admin

Updated 2026-09-22 09:31:49 UTC by Admin