

Fanvil X4U

[Back to Phone Model Examples](#)

```
<?xml version="1.0" encoding="UTF-8"?>
<sysConf>
  <Version>2.0000000000</Version>
  <ap>
    <AutoEtcUrl>https://yourserver.com/graphics/Digibblue.bmp</AutoEtcUrl>
    <AutoPbookUrl>https://yourserver.com/pbx/autoprovision/boot/{${mac}}-
directory.xml</AutoPbookUrl>
  </ap>
  <sip>
    <SIPPort>5060</SIPPort>
    <STUNServer></STUNServer>
    <STUNPort>3478</STUNPort>
    <STUNRefreshTime>50</STUNRefreshTime>
    <SIPWaitStunTime>800</SIPWaitStunTime>
    <ExternNATAddr></ExternNATAddr>
    <RegFailInterval>32</RegFailInterval>
    <SIPPswdEncryption>0</SIPPswdEncryption>
    <StrictBranchPrefix>0</StrictBranchPrefix>
    <VideoMuteAttr>0</VideoMuteAttr>
    <EnableGroupBackup>0</EnableGroupBackup>
    <EnableRFC4475>1</EnableRFC4475>
    <StrictUAMatch>1</StrictUAMatch>
    <CSTAEnable>0</CSTAEnable>
    <NotifyReboot>1</NotifyReboot>
  </sip>
  {line_loop}
    <line index="{${line_m1}}">
      <PhoneNumber>{${username}}</PhoneNumber>
      <DisplayName>{${displayname}}</DisplayName>
      <SipName>{${displayname}}</SipName>
      <RegisterAddr>{${server_host}}</RegisterAddr>
      <RegisterPort>{${server_port}}</RegisterPort>
      <RegisterUser>{${username}}</RegisterUser>
      <RegisterPswd>{${secret}}</RegisterPswd>
```

```
        <RegisterTTL>360</RegisterTTL>
        <EnableReg>1</EnableReg>
    </line>
{/line_loop}
</sip>
</sysConf>
```

Revision #1

Created 2026-09-22 09:31:58 UTC by Admin

Updated 2026-09-22 09:31:58 UTC by Admin